



NEW
Mini-T 13
 Radiant Tube Heater

Benefits/Value:

- 13,000 Btuh
- Ultra low maintenance due to few parts
- Up to 20% energy savings with lower gas usage
- Better heat coverage than traditional brooders
- Variable rate with zone panel
- Easy to clean (power washable)
- Can be hoisted and stored out of the way
- House control available

Comes fully assembled

Easy to hang

Plug and play for current brooders

5 PSI gas pressure

Carbon monoxide output almost undetectable

PATENT PENDING

Mini-T 13 Radiant Tube Heater Specifications

| | | Mini-T 13 EC | Mini-T 13 |
|--|---------------------|-------------------------------------|-----------|
| Rating | | | |
| - Input (Btuh) Single Stage (max./ min.) | | 13,000 / (5 psi) 8,000 / (2 psi) | |
| Tube Length (ft.) | | 3 | |
| Minimum Installation Height (ft.) | | 4 | |
| Ignition | | Pilot | Manual |
| Fuel Consumption (max.): | | | |
| - Liquid Propane Gas (lbs./hr.) | | 0.6 | |
| - Natural Gas (cu. ft. / hr.) | | 13 | |
| Min. Required Ventilation for Heater (CFM) | | 52 | |
| Inlet Gas Supply Pressure | | | |
| - LP Gas min. / max. (in. W.C.) | | 5.0 / 5.0 | |
| - Natural Gas min. / max. (in. W.C.) | | 5.0 / 5.0 | |
| Electrical Supply (Volts / Hz / Phase): | | 120/60/1 | NA |
| Minimum Clearance to Combustibles (in.) | Top | 15 | |
| | Sides | 12 | |
| | Below Radiant Tubes | 36 | |
| Burner Box Material | | Stainless Steel | |
| Reflector Material | | Polished Aluminum | |
| Tube Material | | Calorized Steel | |
| Overall Heater Dimensions (in.) | | | |
| - Length | | 48 | |
| - Width | | 13-5/8 | |
| - Height | | 12-1/4 | |
| Net Weight (lbs.) | | 18 | 17 |
| Shipping Weight (lbs.) | | 22 | 21 |
| 1/2" x 6' Gas Hose | | 0 | |
| Regulator | | 0 | |
| Gas Cock and Piping Hardware | | 0 | |
| Hanging Hardware | | 0 | |

EC = Electronic Control

PATENT PENDING



800-845-3374
FarmerBoyAg.com

