

once

by @signify



PRODUCT CATALOG

once

by Signify



ABOUT US

At Once by Signify, we are more than just your average lighting company. We are the world leader in lighting, with global brands including Once, Interact, and Philips. What sets us apart is our passion for scientific research and innovation, enabling us to constantly push the boundaries and deliver cutting-edge solutions to our clients.

Our team of experts works tirelessly to develop lighting solutions that improve animal welfare, performance and sustainability. We understand that running a farm comes with unique challenges; which is why we offer a range of tailored lighting solutions to help you achieve your goals.

Whether you're looking to optimize productivity or promote animal welfare our team has you covered. Our energy-efficient, environmentally conscious offerings range from basic white lighting to multi-spectral, dynamic solutions with scientifically proven light recipes. We'll help you make your farm more productive, sustainable, and keep your animals healthy and happy.

Let us be your partner in lighting and together we can unlock the full potential of nature and science.



LET'S GET STARTED!

As you scroll through the pages, if you find yourself with questions - don't hesitate to reach out directly. Scan this QR code and use our 'chat live' button in the lower right hand corner of the page. Our customer service team is ready to help you!

TABLE OF CONTENTS

BROILER | BROILER BREEDER PULLET | TURKEY

View All Products and Offerings
Junction-Box Mounted Light for Pullets (JLP)
Multi-Adapter Light for Broilers (MLB)
Multi-Adapter Light Mini for Broilers (MLM-B)
Optient NEW!
NatureDynamics Dome

LAYER | BREEDER

View All Products and Offerings
Straight-Through Feed Line Light (EL)
Junction-Box Mounted Layer Light (JLL)
Multi-Adapter Light for Layers (MLL)
Multi-Adapter Light Mini for Layers (MLM-R)
Tube Light for Layers (TLL)
Tube Light Under-System (TLUS)
Tube Light for Pullets (TLP)
NatureDynamics Dome

SWINE

View All Products and Offerings
Multi-Adapter Light for Swine (MLS)
Multi-Adapter Light Mini for Swine (MLM-S)
Heat Lamps

BIOSECURITY

BioShift

ADAPTERS | ACCESSORIES

Adapter Kits
AgriShift STC
Junction Box

CONTROLLERS | DIMMERS

Controllers
Dimmers
Surge Protectors



What if you could manage your flock through light recipes?

once
by Signify

once

by Signify



**CONTROLLED VIA
SMART PHONE OR FARM
COMPUTER**



**LIGHT RECIPES DESIGNED
FOR ANIMALS BY LEADING
SCIENTISTS AND RESEARCHERS**




**MADE FOR
HARSH CLEANING
ENVIRONMENTS**

Introducing NatureDynamics Dome, a fully controllable lighting system that allows you to adjust the spectrum and intensity through light recipes. Our patented light recipes stimulate bird activity, giving you optimal control over your production results.

WE ARE SIGNIFY, THE WORLD LEADER IN LIGHTING





LIGHT RECIPES TO IMPROVE ANIMAL WELFARE



A light recipe is a specific combination of light intensity, spectrum and schedule designed to achieve desired outcomes. In other words, a light recipe is a set of instructions that tell a lighting system what kind of light to produce and when to produce it.

In poultry farming, specific light recipes can be used to promote many bird performance and welfare-related goals. Examples include encouraging growth, reducing stress and improving egg production. These recipes are

designed based on research that identified optimal light intensity, color and duration for these different outcomes. By using these light recipes, farmers can provide their birds ideal lighting conditions to help them thrive.



once

by  signify

**BROILER
BROILER BREEDER PULLETS
TURKEY**

BROILER, BROILER BREEDER PULLETS, AND TURKEY PRODUCTS AND OFFERINGS



	Broilers, Turkeys and Pullets	Broilers, Turkeys and Pullets	Broilers, Turkeys and Pullets	Broilers and Turkeys	Broilers, Pullets and Turkeys
Product family	Junction-Box Mounted Light for Pullets (JLP)	Multi-Adapter Light for Broilers (MLB)	Multi-Adapter Light Mini for Broilers (MLM-B)	Optient NEW!	Nature Dynamics Dome
Spectrum/Light Recipe	Dim-to-Blue	Dim-to-Blue	Dim-to-Blue	White	Junglite
Lumen output	930	1400	1000	240	1200
Power	8W	14W	10W	2W	11W
Efficacy	110 lm/w	100 lm/w	100 lm/w	120 lm/w	110 lm/w
Color Temperature	4300K	4500K (Brood) 5000K (Grow out)	4500K (Brood) 5000K (Grow out)	5000K	Tunable
App controlled	No	No	No	No	Interact Agriculture App
Designed for Animal Use	Yes	Yes	Yes	Yes	Yes
Benefits	Improves performance compared to white light. Promotes calmer birds.	Improves performance compared to white light. Promotes calmer birds.	Improves performance compared to white light. Promotes calmer birds.	Improves FCR and promotes freedom of choice with gradient lighting.	Optimal lighting at every age improves FCR and welfare. Reduces stress/fear and promotes calmer birds.
Mounting	Junction box	Screw-in type and Base unit with junction box	Screw-in type and Base unit with junction box	Mounted with special accessories	Base unit with Junction Box
IP Rating (water and dust resistance)	IP66	IP66	IP66	IP66	IP65
IK Rating (product resistance to damage)	IK07	IK07	IK07	IK05	IK07
Dimmability	1-100%	1-100%	1-100%	No dimming	0-100%
Certifications (compliant with country regulations)	UL/CSA	UL/CSA	UL/CSA	UL/CSA	UL/CSA
Expected Product Lifetime	L70 @ 50k hours	L70 @ 50k hours	L70 @ 50k hours	L70 @ 50k hours	L70 @ 50k hours
Warranty	5 years	5 years	5 years	5 years	5 years

8W Junction-Box Mounted Light for Pullets (JLP)

Spectrum/Light Recipe: Dim-to-Blue

Features:

- 8W, 120VAC, 930 lm, 180 Degree Tall Lens (very wide beam angle)
- Installation: Junction Box
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 107mm diameter x 63mm tall. Weight per piece 0.141kg
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours, 5 years

Order number: SKU 1000000579

Description: JLP 800/WB20 120V JB/T VWB Gen 3



Product also used for
Broiler Breeder Pullets



13W Multi-Adapter Light for Broilers (MLB)

Spectrum/Light Recipe: Dim-to-Blue

Features:

- 13W, 230VAC, 1400 lm, 4500K, very wide beam angle
- Installation: Screw Base
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 87.5mm diameter x 167mm tall. Weight per piece 0.318kg.
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, UL/CSA certified
- Warranty: Rated life >50,000 hours and 3 years

Order number: SKU 1000000815

Description: MLB 1350/WB20 230V EB/T VWB Gen 3



Product also used for Pullets and Turkeys

Screw Base



13W Multi-Adapter Light for Broilers (MLB)

Spectrum/Light Recipe: Dim-to-Blue

Features:

- 13W, 230VAC, 1400 lm, 4500K, efficacy 110lm/W, very wide beam angle
- Installation: Base Unit
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 87.5mm diameter x 107mm tall. Weight per piece 0.271kg
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 3 years

Installation options include junction box mount, Jelly jar mount or suspension (drop-cord) mount using MLM adapters (sold separately)

Order number: SKU 000000728

Description: MLB 1350/WB20 230V BU/T VWB Gen 3



Product also used for Pullets and Turkeys

Base Unit



Mounting adapter
required for installation
- sold separately

14W Multi-Adapter Light for Broilers (MLB)

Spectrum/Light Recipe: Full Spectrum with Blue

Features:

- 14W, 120VAC, 1400 lm, 4500K, efficacy 100lm/W, very wide beam angle
- Installation: Screw Base
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 87.5mm diameter x 167mm tall, Weight per piece 0.318kg
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Rating and Certifications: IP66, IK07 impact rating, UL/CSA certified
- Warranty: Rated life >50,000 hours, 5 years

Included E26 screw base adapter allows installation onto existing screw base fixtures

Order number: SKU 1000000490

Description: MLB 1400/WB20 120V EB/T VWB Gen 3



Product also used for
Broiler Breeder Pullets

Screw Base



14W Multi-Adapter Light for Broilers (MLB)

Spectrum/Light Recipe: Dim-to-Blue

Features:

- 14W, 120VAC, 1400 lm, 4500K, very wide beam angle
- Installation: Base Unit
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 87.5mm diameter x 106.5mm tall. Weight per piece 0.271kg
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, UL/CSA certified
- Warranty: Rated life >50,000 hours, 5 years

Order number: SKU 1000000580

Description: MLB 1400/WB20 120V BU/T VWB Gen 3



Product also used for Pullets and Turkeys

Base Unit



Mounting adapter
required for installation
- sold separately

10W Multi-Adapter Light Mini for Broilers (MLM-B)

Spectrum/Light Recipe: Dim-to-Blue

Features:

- 10W, 120VAC, 4700k, 1000 lm, efficacy 110 lm/W, extra wide beam angle
- Installation: Screw Base
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 81mm diameter x 143mm tall. Weight per piece 0.177kg
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

Included E26/E27 screw base adapter allows installation onto existing screw base fixtures

Order number: SKU 1000000805

Description: MLM 1000/WB20 120V EB/T VWB Gen 3



Product also used for Pullets

Screw Base



10W Multi-Adapter Light Mini for Broilers (MLM-B)

Spectrum/Light Recipe: Dim-to-Blue

Features:

- 10W, 120VAC, 4700k, 1000 lm, efficacy 110 lm/W, extra wide beam angle
- Installation: Base Unit
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 86mm diameter x 82mm tall. Weight per piece 0.152kg
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK06, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

*Installation options include junction box mount, Jelly jar mount or suspension (drop-cord) mount using MLM adapters (sold separately)

Order number: SKU 1000000803

Description: MLM 1000/WB20 120V BU/T VWB Gen 3



Product also used for Pullets

Base Unit



Mounting adapter
required for installation
- sold separately

NEW! Optient for Broilers

Spectrum/Light Recipe: White-light gradient lighting system

Features:

- 24V, 2W, 5000K, Efficacy 120 lm/W, 240lm
- Installation: Mount on feedline anti-roostwire; accessories are required
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 80.6mm diameter x 41.2mm tall. Weight per piece 0.072kg
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK05, IEC Class II, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

SKU: 1000001064

Description: Optient 220 24VDC 5000K



Product also used for Turkeys



NatureDynamics Dome - 120V

Spectrum/Light Recipe: Multispectral light output, 3 channel, optimized for the Junglite light recipe


Features:

- 11W, 120VAC, 60Hz, 1200 lm, efficacy 110 lm/W, extra wide beam angle
- Installation: Base unit to be used in combination with a junction box (Adapter sold separately)
- Controlled through a barn computer or smart phone – via the Interact Agriculture App
- Dimming: Recipe controlled, 0 to 100%
- Shockproof plastic cover
- Product size and weight: 87.5mm diameter x 145mm tall. Weight per piece 0.244kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP65, IK07 impact rating, IEC Class II, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

*Suitable for combination with lighting fixture ND Dome JB base (to be ordered separately).

Order number: SKU 1000000601

Description: ND-DOME 1250/MS30 120V IA1 VWB



Product also used for Pullets and Turkeys

Base Unit



NatureDynamics Dome - 230V

Spectrum/Light Recipe: Multispectral light output, 3 channel, optimized for the Junglite light recipe

Features:

- 11W, 230V 50/60Hz, 1200 lm, efficacy 110 lm/w, extra wide beam angle
- Installation: Install to IUL Junction Box
- Controlled through a barn computer or smart phone – via the Interact Agriculture App
- Dimming: Recipe controlled, 0 to 100%
- Shockproof plastic cover
- Product size and weight: 87mm diameter x 145mm tall. Weight per piece 0.244kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK03, IEC Class II, CE/UKCA certified
- Warranty: Rated life >50,000 hours and 5 years

Order number: SKU 1000000828

Description: ND-DOME 1250/MS30 230V IA1 VWB



Product also used for Pullets and Turkeys



BOOSTS PRODUCTIVITY | UP TO 70% ENERGY-SAVINGS | IMPROVES ANIMAL WELFARE

optient

PATENT PENDING

INTRODUCING THE NEW REVOLUTIONARY GRADIENT LIGHTING SOLUTION THAT IS ALL ABOUT RESULTS



Our scientists and engineers took a bird's eye view to develop a gradient lighting solution that promotes freedom of choice and optimal performance in commercial broiler houses. It can improve feed conversion and animal welfare, and decrease energy usage by up to 70%. Optient, our patent-pending lighting solution, offers best-in-class performance and animal welfare.



WE ARE SIGNIFY, THE WORLD LEADER IN LIGHTING



once

by ©signify

**LAYER
BREEDER**

LAYER AND BREEDER PRODUCTS AND OFFERINGS

Point source lights for ceilings



	Layers, Breeders	Layers, Breeders	Layers, Breeders	Layers, Breeders
Product family	Junction-Box Mounted Layer Light (JLL)	Multi-Adapter Light for Layers (MLL)	Multi-Adapter Light Mini for Layers (MLM-R)	NatureDynamics Dome for Layers
Spectrum/Light Recipe	Dim-to-Red	Dim-to-Red	Dim-to-Red	Redlite
Lumen output	610	900	610	1100
Power	8W	11W	8W	12W
Efficacy	76 lm/w	80 lm/w	76 lm/w	92 lm/w
Color Temperature	2700K	2900K	2700K	Tunable
App controlled	No	No	No	Interact Agriculture App
Dimmer required	Yes	Yes	Yes	No
Designed for Animal Use	Yes	Yes	Yes	Yes
Benefits	Improves bird performance and reduces bird stress compared to white light.	Improves bird performance and reduces bird stress compared to white light.	Improves bird performance and reduces bird stress compared to white light.	Optimal lighting throughout production with improved performance and reduced bird stress. Enhances bird management and training with custom light recipes.
Mounting	Junction Box	Screw-in, jelly jar, junction box and suspension	Screw-in, jelly jar, junction box and suspension	Junction box mounted with an adapter
IP Rating (water and dust resistance)	IP66	IP66	IP66	IP65
IK Rating (product resistance to damage)	IK07	IK07	IK07	IK07
Dimmability	1-100%	1-100%	1-100%	0-100%
Certifications (compliant with country regulations)	UL/CSA	UL/CSA	UL/CSA	UL/CSA
Expected Product Lifetime	L70 @ 50k hours	L70 @ 50k hours	L70 @ 50k hours	L70 @ 50k hours
Warranty	5 years	5 years	5 years	5 years

LAYER AND BREEDER PRODUCTS AND OFFERINGS

Tube lights for in-system and under-systems



	Layers, Breeders	Pullets	Layers, Breeders
Product family	Tube Light for Layer (TLL)	Tube Light for Pullets (TLP)	Tube Light Under-System (TLUS)
Application	In-system	In-system	Under-system
Sizes	60", 97", 110", 150" & 194"	60", 97" and 194"	55", 91" and 97"
Spectrum/Light Recipe	Dim-to-Red	Junglite Green	Cool White
Lumen output	170 and 340	260 and 520	600 and 1200
Power	2.9W and 5.8W	3.5W and 7W	4.2W and 8.4W
Efficiency	60 lm/w	75 lm/w	Up to 140 lm/w
Color Temperature	2200K	8500K	5000K
Designed for Animal Use	Yes	Yes	Yes
Dimmer required	Yes	Yes	Yes
Benefits	Improves bird performance and reduces bird stress compared to white light.	Improve animal welfare during brood phase.	Bright white under-system light discourages floor egg laying
Mounting	Starter/Extension cord Tubes	Starter/Extension cord Tubes	Starter/extension cord + stringer T connections
IP Rating (water and dust resistance)	IP66	IP66	IP66
IK Rating (product resistance to damage)	IK06	IK06	IK06
Dimmability	1-100%	1-100%	1-100%
Certifications (compliant with country regulations)	UL/CSA	UL/CSA	UL/CSA
Expected Product Lifetime	L70 @ 50k hours	L70 @ 50k hours	L70 @ 50k hours
Warranty	5 years	5 years	5 years

8W Junction-Box Mounted Layer Light (JLL)

Spectrum/Light Recipe: Dim-to-Red

Features:

- 8W, 120VAC, 2700K, 610 lm, short Lens, efficacy 76 lm/w, very wide beam angle
- Installation: Junction Box
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 107mm length x 22mm tall. Weight per piece 0.121kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

Order number: SKU 1000000790

Description: JLL 600/WR20 120V JB/S VWB Gen 3



Product also used for Layer Pullets,
Broilers, and Breeders



Junction-Box Mounted Layer Light (JLL)

Spectrum/Light Recipe: Dim-to-Red

Features:

- 8W, 120VAC, 2700K, 610 lm, tall lens, efficacy 76 lm/w, very wide beam angle
- Installation: Junction box
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 107mm length x 63mm tall. Weight per piece 0.141kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

Order number: SKU 1000000757

Description: JLL 575/WR20 120V JB/T VWB Gen 3



Product also used for Layer Pullets,
Broilers, and Breeders



11W Multi-Adapter Light for Layers (MLL)

Spectrum/Light Recipe: Full Spectrum Dim-to-Red

Features:

- 11W, 120VAC, 2900K, 900 lm, tall lens, efficacy 80lm/w, very wide beam angle
- Installation: Edison Base
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 87.5mm length x 167mm tall. Weight per piece 0.318kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

Includes E26 screw base adapter allows installation onto existing screw base fixtures

Order number: SKU 1000000603

Description: MLL 900/WR 120V EB/T VWB GEN 3



Product also used for Layer Pullets, Broilers, and Breeders

Screw Base



11W Multi-Adapter Light for Layer (MLL)

Spectrum/Light Recipe: Full Spectrum Dim-to-Red

Features:

- 11W, 120VAC, 2900K, 900 lm, tall lens, efficacy 80lm/w, very wide beam angle
- Installation: Junction box, jelly jar and suspension (drop cord)
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 87.5mm length x 106.5mm tall. Weight per piece 0.271kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

*Installation options include junction box mount, jelly jar or suspension (drop cord) mount using MLM adapters (sold separately) *

Order number: SKU 1000000470

Description: MLL 900/WR 120V BU/T VWB GEN 3



Product also used for Layer Pullets, Broilers, and Breeders

Base Unit



Mounting adapter required for installation - sold separately

12W Multi-Adapter Light for Layers

Spectrum/Light Recipe: Full Spectrum Dim-to-Red

Features:

- 12W, 230VAC, 2900K, 1000 lm, efficacy 83 lm/W, very wide beam angle
- Installation: Junction box, jelly jar and suspension (drop cord)
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 87.5mm length x 106.5mm tall. Weight per piece 0.271kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 3 years

*Installation options include junction box mount, jelly jar mount or suspension (drop-cord) mount using MLM adapters (sold separately) *

Order number: SKU 1000000806

Description: MLL 1000/WR 230V BU/T VWB GEN 3



Product also used for Layer Pullets, Broilers, and Breeders

Base Unit



8W Multi-Adapter Light Mini for Layers (MLM-R)

Spectrum/Light Recipe: Dim-to-Red

Features:

- 8W, 230VAC, 2500K, 600 lm, efficacy 75 lm/W, very wide beam angle
- Installation: Screw Base
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 86mm length x 143mm tall. Weight per piece 0.177kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

Included E26 screw base adapter allows installation onto existing screw base fixtures

Order number: SKU 1000000773

Description: MLM 600/WER20 120V EB/T VWB



Product also used for Layer Pullets, Broilers, and Breeders

Screw Base



8W Multi-Adapter Light Mini for Layers (MLM-R)

Spectrum/Light Recipe: Dim-to-Red

Features:

- 8W, 120VAC, 2600K, 600 lm, efficacy 75 lm/W, very wide beam angle
- Installation: Base Unit
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 86mm length x 82.5mm tall. Weight per piece 0.152kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

*Installation options include junction box mount, Jelly jar mount or suspension (drop-cord) mount using MLM adapters (sold separately) *

Order number: SKU 1000000727

Description: MLM 600/WER20 120V BU/T VWB



Product also used for Layer Pullets, Broilers, and Breeders

Base Unit



Mounting adapter required for installation - sold separately

8W Multi-Adapter Light Mini for Layers (MLM-R)

Spectrum/Light Recipe: Dim-to-Red

Features:

- 8W, 230VAC, 2700K, 650 lm, efficacy 80 lm/W, very wide beam angle
- Installation: Screw Base
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 86mm length x 143mm tall. Weight per piece 0.177kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 3 years

* Included E26 screw base adapter allows installation onto existing screw base fixtures*

Order number: SKU 1000000818

Description: MLM 600/WR20 230V EB/T VWB Gen



Product also used for Layer Pullets, Broilers, and Breeders

Base Unit



8W Multi-Adapter Light Mini for Layers (MLM-R)

Spectrum/Light Recipe: Dim-to-Red

Features:

- 8W, 230VAC, 2700K, 650 lm, efficacy 80 lm/W, very wide beam angle
- Installation: Screw Base
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 86mm length x 82mm tall. Weight per piece 0.152kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 3 years

* Installation options include junction box mount, Jelly jar mount or suspension (drop-cord) mount using MLM adapters (sold separately)

Order number: SKU 1000000748

Description: MLM 600/WR20 230V BU/T VWB Gen 3



Product also used for Layer Pullets, Broilers, and Breeders

Base Unit



Mounting adapter required for installation - sold separately

NatureDynamics DOME - 120V

Spectrum/Light Recipe: Multispectral light output, 3 channel, optimized for Redlite recipe

Features:

- 12W, 120V, 1100 lm, efficacy 92 lm/W, extra wide beam angle
- Installation: Base unit to be used in combination with a junction box (Adapter sold separately)
- Shockproof plastic cover
- Dimming: Recipe controlled, 0 to 100%
- Product size and weight: 87mm diameter x 145mm length. Weight per piece 0.244kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK03 impact rating, IEC Class II, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

*Suitable for combination with lighting fixture ND Dome Junction box adapter kit base (to be ordered separately) *

Order number: SKU 1000000967

Description: ND-DOME 900/MS30 120V IA1 VWB



Product also used for Layer Pullets, Broilers, and Breeders

Base Unit



NatureDynamics DOME - 230V

Spectrum/Light Recipe: Multispectral light output, 3 channel, optimized for Redlite color recipe

Features:

- 12W, 230V, 1100 lm, efficacy 92 lm/W, extra wide beam angle
- Installation: Base unit to be used in combination with a junction box (Adapter sold separately)
- Shockproof plastic cover
- Dimming: Recipe controlled, 0 to 100%
- Product size and weight: 87mm diameter x 145mm length. Weight per piece 0.244kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK03 impact rating, IEC Class II, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

*Suitable for combination with lighting fixture IUL base (to be ordered separately) *

Order number: SKU 1000000966

Description: ND-DOME 900/MS30 230V IA1 VWB



Product also used for Layer Pullets, Broilers, and Breeders

Base Unit



Single Tube - Tube Light for Layers (TLL)

Spectrum/Light Recipe: Dim-to-Red

Features:

- 3W, 120V, 60Hz, 2200K, 170 lm, efficacy 57 lm/W, very wide beam angle
- Installation: Single tube assembly with cables is 60" long (tubes are connected in series)
- Dimming: Fully dimmable
- Product size and weight: 26.6mm diameter x 1382mm length. Weight per piece 0.25kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IK07 impact rating, IEC Class II, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years


*Required accessories: starter/extension cable and end cap

Order number: SKU 1000000849

Description: TLL 168/WR40 120V 1T/60 WB Gen 3



Product also used for Layer Pullets, Broilers, and Breeders



Double Tube - Tube Light for Layers (TLL)

Spectrum/Light Recipe: Dim-to-Red


Features:

- 6W, 120V, 60Hz, 2200K, 340 lm, efficacy 57 lm/W, very wide beam angle
- Installation: Double tube assembly with cables is 110" long (tubes are connected in series)
- Dimming: Fully dimmable
- Product size and weight: 26.6mm diameter x 2761mm length. Weight per piece 0.56kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class II, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years


*Required accessories: starter/extension cable and end cap

Order number: SKU 1000000841

Description: TLL 331/WR40 120V 2T/110 WB Gen 3



Product also used for Layer Pullets, Broilers, and Breeders



Double Tube - Tube Light Under-System (TLUS)

Spectrum/Light Recipe: Bright White

Features:

- 8.5W, 120V, 60Hz, 5000K, 1200 lm, efficacy 140 lm/W, very wide beam angle, dual asymmetric beam spread
- Installation: Double tube - 97" long (in-series) | Double tube - 91" long (stringer-tube)
- Dimming: Fully dimmable
- Product size and weight: 25.6mm diameter x 2463mm length. Weight per piece 0.632kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK06 impact rating, IEC Class II, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

*Accessories required: starter cable and end cap, stringer (when applicable)


Order number:

In-series SKU 1000000951 and stringer-tube version: SKU 1000001065

Description: TLUS 1240/W50 120V 2T/097 WB Gen 3



Product also used for Layer Pullets



Single Tube - Tube Light Under-System (TLUS)

Spectrum/Light Recipe: Bright White

Features:

- 4.2W, 120V, 60Hz, 5000K, 600 lm, efficacy 140 lm/W, very wide beam angle, dual asymmetric beam spread
 - Installation: Single tube with cables is 55" long
 - Dimming: Fully dimmable
 - Product size and weight: 25.6mm diameter x 1397mm length. Weight per piece 0.353kg
 - Operating temperature -10°C to 40°C / -4°F to 104°F
 - Ratings and Certifications: IP66, IK06 impact rating, IEC Class II, UL/CSA certified
 - Warranty: Rated life >50,000 hours and 5 years
- *Accessories required: starter cable and end cap

Order number: SKU 1000000952

Description: TLUS 620/W50 120V 1T/055 WB Gen 3



Product also used for Layer Pullets, Broilers, and Breeders



Single Tube - Tube Light for Pullets (TLP)

Spectrum/Light Recipe: For use with the Junglite light recipe


Features:

- 3.5W, 120V, 60 Hz, 8500K, 250 lm, efficacy 72 lm/W, very wide beam angle spread
- Installation: Single tube with cable is 60" long (tubes are connected in series)
- Dimming: Fully dimmable with sunrise/sunset function
- Product size and weight: 26.6mm diameter x 1524mm length. Weight per piece 0.26kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK06 impact rating, IEC Class II, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

*Accessories required: starter/extension cable and end cap

Order number: SKU 1000000505

Description: TLP 250/WB40 120V 1T/60WB Gen 3



Product also used for Layer Pullets, Broilers, and Breeders



Double Tubes - Tube Light for Pullets (TLP)

Spectrum/Light Recipe: Junglite Green

Features:

- 7W, 120V, 60 Hz, 8500K, 500 lm, efficacy 72 lm/W, very wide beam angle
- Installation: Double tube with cables is 194" long (tube is connected in series)
- Dimming: Fully dimmable with sunrise/sunset function
- Product size and weight: 26.6mm diameter x 1524mm length. Weight per piece 0.75kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK06 impact rating, IEC Class II, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

*Accessories required: starter/extension cable with end cap

Order number: SKU 1000000551

Description: TLP 500/WB40 120V 2T/194 WB



Product also used for Layer Pullets, Broilers, and Breeders



Straight-Through Feed Line Light (EL)

Spectrum/Light Recipe: Full Spectrum Dim-to-Red

Features:

- 3W, 120VAC, 5000K, 175 lm, very wide beam angle
- Installation: aisle lighting, using standard ½" PVC conduit body
- Dimming: Smooth dimming 100% to 5% using the Once Control/Dimmer
- Product size and weight: 103.9mm length x 34.6mm wide x 11mm tall. Weight per piece 0.042kg/0.094Lbs
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IEC protection: Class I, Shock resistance rating: IK03
- Warranty: Rated life >50,000 hours and 5 years

Order number: SKU 1000000611

Description: EL 132/WR50 120V HW WB



Product also used for
Layer Pullets

Straight Through Feed





once

by  signify

SWINE

SWINE PRODUCTS AND OFFERINGS



	Swine	Swine	Swine
Product family	Multi-adapter light mini for swine	Multi-adapter light for swine	Heat Lamps
Spectrum/Light Recipe	Dim-to-Red	Dim-to-Red	Clear
Lumen output	1100	1500	
Power	10W	14W	125W and 175W Available
Efficacy	110 lm/w	110 lm/w	
Color Temperature	4900K	5000K	
Sustainable	2/3	2/3	Yes
Designed for Animal Use	Yes	Yes	Yes
Benefits	Dusk and dawn simulation to reduce stress. Monochromatic red at night as a utility light won't interfere with circadian rhythm.	Dusk and dawn simulation to reduce stress. Monochromatic red at night as a utility light won't interfere with circadian rhythm.	Ensure your pigs receive the appropriate warmth essential for a great start to their health and well-being.
Mounting	Base unit with Junction box	Base unit with junction box	
IP Rating (water and dust resistance)	IP66	IP66	IP66
IK Rating (product resistance to damage)	IK07	IK07	Shatter-proof
Dimmability	1%-100%	1%-100%	Dimmable
Certifications (compliant with country regulations)	UL/CSA	UL/CSA	IEC Class II, Shatter-proof
Expected Product Lifetime	L70 @ 50k hours	L70 @ 50k hours	5000 hours
Warranty	5 years	5 years	90 days

10W Multi-Adapter Light Mini for Swine (MLM-S)

Spectrum/Light Recipe: Dim-to-Red

Features:

- 10W, 120V, 4900K, 1100 lm, efficacy 110 lm/W, wide beam angle
- Installation: Base Unit
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 86mm diameter x 82.5mm length. Weight per piece 0.152kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

***Installation options include junction box mount, Jelly jar mount or suspension (drop-cord) mount using MLM adapters (sold separately) ***

Order number: SKU 1000000772

Description: MLS 1500/SWR 120V BU/T VWB GEN 3

Base Unit



Mounting adapter
required for installation
- sold separately

14W Multi-Adapter Light for Swine (MLS)

Spectrum/Light Recipe: Dim-to-Red

Features:

- 14W, 120V, 5000K, 1500 lm, efficacy 110 lm/W, Tall Lens with very wide beam angle
- Installation: Base Unit
- Dimming: Smooth dimming 100% to 1% using the Once Control/Dimmer
- Product size and weight: 87.5mm diameter x 106.5mm tall. Weight per piece 0.280kg
- Operating temperature -10°C to 40°C / -4°F to 104°F
- Ratings and Certifications: IP66, IK07 impact rating, IEC Class I, UL/CSA certified
- Warranty: Rated life >50,000 hours and 5 years

***Installation options include junction box mount or Jelly jar mount using MLM adapters (sold separately)**

Order number: SKU 1000000602

Description: MLS 1500/SWR 120V BU/T VWB GEN 3

Base Unit



Mounting adapter
required for installation
- sold separately

125W Heat Lamp, Clear

Spectrum/Light Recipe: White

Features:

- 125W, 120V, 60 Hz, infrared, PAR 38, Clear
- Incandescent PA
- Installation: Screw base
- Dimming: Dimmable heat lamp
- Product size and weight: 121mm diameter x 135mm tall. Weight per piece 0.308kg
- Ratings and Certifications: IEC Class II, Shatter-proof
- Warranty: Rated life >5000 hours and 90 days

Order number: SKU 1000000993

Description: IR 125PAR38/HEAT/CL/AG 120V



175W Heat Lamp, Clear

Spectrum/Light Recipe: White

Features:

- 175W, 120V, 60 Hz, infrared, PAR 38, Clear
- Incandescent PA
- Installation: Screw base
- Dimming: Dimmable heat lamp
- Product size and weight: 121mm diameter x 135mm tall. Weight per piece 0.308kg
- Ratings and Certifications: IEC Class II, Shatter-proof
- Warranty: Rated life >5000 hours and 90 days

Order number: SKU 1000000767

Description: IR 175PAR38/HEAT/CL/AG 120V 12/1





once

by ignify

BIOSECURITY

BioShift UV-C Chamber, Small Unit

- Small chamber with two doors (one in the front and one in the back)
- 120-240V, 50/60Hz
- Outside dimensions 23 L x 29.5 W x 23.6 H inches (585 L x 750 W x 600 H mm)
- Stainless steel
- Touch-screen control panel
- IP50, safety class I, UL/CSA Certified
- UV 20W Light bulbs (4)
- Net weight: 50 kg/100 lbs
- Warranty: 2 years

Includes: drip tray, 1-pack of UVC intensity monitoring cards, safety glasses, 1.5m power cable

Order number: SKU 1000000372



BioShift UV-C Chamber, Extra-large Unit

- Extra-large chamber with two doors (one in the front and one in the back)
- 120-240V, 50/60Hz
- Outside dimensions 46.5 L x 30 W x 72 H inches (1180 L x 762 W x 1828 H mm)
- Stainless steel
- Touch-screen control panel
- IP50, safety class I, UL/CSA Certified
- UV 40W Light bulbs (18)
- Net weight: 170 kg/375 lbs
- Warranty: 2 years

Includes: drip tray, 1-pack of UVC intensity monitoring cards, safety glasses, 4 removable racks

Order number: SKU 1000000375



INTRODUCING THE BIOSHIFT, A TOOL FOR BIOSECURITY



A ONCE study on biosecurity in agriculture proved that a 5-minute exposure to UVC disinfection, reduced all common bacteria and viral load by a minimum of 4 log or 99.99%.

The Once BioShift is a stainless steel chamber that houses Ultraviolet-C (UVC) light.

- Chemical-free uv disinfection to maximize bio-security protocols
- Heavy-duty stainless-steel chamber
- Rugged shelving to support heavy items
- A single-entry and exit (synchronized locking) to ensure only treated items can enter a facility
- Safety-tested to ensure that UVC does not leak
- Available in two sizes; a small and extra-large unit



once

by ignify

**ADAPTORS
AND ACCESSORIES**

These items are sold separately.

Edison Base Adapter Kit


The Edison Base adapter kit can be used with all ML and MLM-series base units

Kit Specs:

- Standard E26 screw base
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Product weight per piece 0.050kg/0.110lbs

Order number: SKU 1000000477

Description: MLEB 00 ADP KIT



Multi-Adapter Light Mini, Junction Box (JB) Adapter Kit

The Junction Box adapter kit can be used to mount ML and MLM-series to existing ONCE junction box. Adapter supplied with ONCE quick connect wire harness.


Kit Specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F
- 110mm diameter x 18mm tall
- Product weight per piece 0.054kg/0.118lbs

Order number: SKU 1000000426

Description: MLM JB 00 ADP KIT

Junction box sold separately see below.*



Junction Box

Plastic Junction box suitable for new installations or refurbishments in barns.

Featuring mounting tabs, (5) 3/4 NPT threaded holes with knockouts and standard cover hole pattern for mounting ML series adapters.

Product Specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F,
- Product weight per piece 0.25kg/0.55lbs

Order number: SKU 1000000410

Description: RND NM WP Box (5) 3/4 IN. Out KO - Gray



Multi-Adapter Light Mini, Jelly Jar (JJ) Adapter Kit


The Jelly Jar adapter kit can be used to mount ML and MLM-series to existing Jelly Jar type of fixtures. The adapter kit contains (1) 84MM screw base and (1) E26 to ML quick-connect wire harness assembly.

Kit Specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F
- 110mm diameter x 58.5mm tall
- Product weight per piece 0.079kg/0.173lbs

Order number: SKU 1000000418

Description: MLM JJ 00 ADP KIT



NatureDynamics Dome JB Adapter Kit (Qty 10 Kits)

Used between NatureDynamics DOME and ONCE US junction box, this kit contains (1) threaded adapter, (2) silicone sealing gaskets and (4) mounting screws.

Kit Specs:

- Box of 10 kits
- Operating temperature -20°C to 40°C / -4°F to 104°F

Order number: SKU1000000853

Description: ND DOME JB Adapter Kit 10 (Qty 10 Kits)



These items are sold separately.

once

by signify

Multi-Adapter Light Mini, Hard Wire (HW) adapter


The Hard Wire adapter can be used with all ML series base units. The adapter suspends a ML or MLM light two meters from the junction box.

Product specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F
- 72mm diameter x 2000mm tall
- Product weight per piece 0.236kg/0.520Lbs
- Also available in 1m and 2ft. lengths

Order number: SKU 1000000473

Description: MLM HW 00 2M ADP KIT



Stringer Adapter (STC) - 1m overall length


The 1m Stringer Adapter attaches a ML or MLM-series light to a STC stringer. The assembly is equipped with the ML and MLM quick-connect wire harness.

Product specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F
- Product weight per piece 0.30kg/0.66lbs

Order number: SKU 1000000640

Description: ML STA 00 1M



Stringer Adapter (STC) - 2m overall length


The 2m Stringer Adapter attaches a ML or MLM-series light to a STC stringer. The assembly is equipped with the ML and MLM quick-connect wire harness.

Product specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F
- Product weight per piece 0.60kg/1.32lbs

Order number: SKU 1000000406

Description: ML STA 00 2M



NatureDynamics Dome Drop Cord Kit

The 2m Dome Drop Cord suspends a NatureDynamics Dome light 2m from a ceiling-mounted junction box. This contains (1) drop cord, 1 silicone gasket and (2) lever-lock connectors.

Kit specs:

- Operating temperature -10°C to 40°C / 14°F to 104°F
- Product weight per piece 0.35kg/0.77lbs

Order number SKU: 1000000931

Description: ND Dome Drop Cord 2m



These items are sold separately.

Stringer Adapter (STC) - 3m overall length


The 3m Stringer Adapter attaches a ML or MLM-series light to a STC stringer. The assembly is equipped with the ML and MLM quick-connect wire harness.

Product specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F. P
- Product weight per piece 0.90kg/1.98lbs.

Order number: SKU 1000000562

Description: ML STA 00 3M



Stringer Adapter (STC) - 12" overall length


The 12 inches Stringer Adapter attaches a ML or MLM-series light to a STC stringer. The assembly is equipped with the ML and MLM quick-connect wire harness.

Product specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F
- Product weight per piece 0.25kg/0.55lbs

Order number: SKU 1000000641

Description: ML STA 00 1FT



These items are sold separately.

once

by  signify

Starter Cable - 4ft OAL

The STC Starter cable is used to connect a power source to the STC stringer cable. Featuring a female SC31 connector on one end, stripped wire leads on the other end. This 14AWG 3 conductor cable cable is 4ft in length.

Product specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F
- Product weight per piece 0.35kg/0.77lbs
- Female SC31 connector

Order number: SKU 1000000642

Description: ML STR 00 4FT



Stringer Cable (STC) - 80ft

The Stringer Cable is a fixed length cable with T connections for attachment of Drop cords.

Product specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F.
- Product weight per piece 3.78kg/8.316lbs
- (10) T Connections at 8ft spacing
- 3-pin male SC31 connector

Order number: SKU 1000000420

Description: ML STC 00 24M 10C

Stringer 80 ft



Stringer Cable (STC) - 100ft

The Stringer Cable is a fixed length cable with T connections for attachment of Drop cords.

Product specs:

- Operating temperature -20°C to 40°C / -4°F to 104°F
- Product weight per piece 4.725kg/10.395lbs
- (10) T Connections at 10ft spacing
- 3-pin male SC31 connector

Order number: SKU: 1000000639

Description: ML STC 00 30M 10C

Stringer 100 ft





once

by ignify

**CONTROLLERS
AND DIMMERS**

Controller, LCL, 120VAC - 60 Hz

A farm lighting controller with two built-in dimming channels. Featuring: AC phase-cut dimming, (2) 1,000 W, 8.34 amp dimming channels, programmable light recipes up to 500 days (20 light events per day).

Product specs:

- 120 VAC, 60 Hz
- 221mm Width x 269mm Length x 139mm Depth
- Operating temperature 0°C to 40°C / 32°F to 104°F
- Product weight per piece 3.00kg/6.60lbs
- Warranty: 36-months

Order number: SKU 1000000479

Description: AGMD 00 120V-60Hz



Dimmer, LEL, 120VAC

A farm lighting two-channel dimmer featuring: AC phase-cut dimming, (2) 1,000 W, 8.34 amp dimming channels. Controlled by farm computer, 0-10V DC input signal or manually.

Product specs:

- 120 VAC, 60 Hz
- 221mm Width x 269mm Length x 139mm Depth
- Operating temperature 0°C to 40°C / 32°F to 104°F
- Product weight per piece 3.00kg/6.60lbs
- Warranty: 36-months

Order number: SKU 1000000464

Description: AGSD 00 120V-60Hz



Controller, LCL, 230VAC - 50 Hz

A farm lighting controller with two built-in dimming channels. Featuring: AC phase-cut dimming, (2) 1,000 W, 4.1 amp dimming channels, programmable light recipes up to 500 days (20 light events per day).

Product specs:

- 230VAC, 50 Hz
- 221 mm Width x 269mm Length x 139mm Depth
- Operating temperature 0°C to 40°C / 32°F to 104°F
- Product weight per piece 3.00kg/6.60lbs
- Warranty: 36-months

Order number: SKU 1000000912

Description: AGMD 00 230V-50Hz



Controller, LCL, 230VAC - 60 Hz

A farm lighting controller with two built-in dimming channels. Featuring: AC phase-cut dimming, (2) 1,000 W, 4.1 amp dimming channels, programmable light recipes up to 500 days (20 light events per day).

Product specs:

- 230VAC, 60 Hz
- 221mm Width x 269mm Length x 139mm Depth
- Operating temperature 0°C to 40°C / 32°F to 104°F
- Product weight per piece 3.00kg/6.60lbs
- Warranty: 36-months

Order number: SKU1000000863

Description: AGMD 00 230V-60Hz



LED Surge Protector

A wall-mounted surge protector with single phase protection and LED indicator.

Product specs:

- 120-277 VAC, 50/60 Hz
- 20 KV max surge
- 50 mm Width x 60 mm Length x 34 mm Depth
- Operating temperature: -35C to 75C/-30F to 165F
- Product weight per piece: 0.31lb/0.14kg
- Ratings and Certifications: UL/CSA certified, NEMA 6P rated

Order number: SKU 1000000968

Description: Surge protector with LED indicator



Precision Dimmer - 120VAC


A farm lighting two-channel dimmer featuring: AC phase-cut dimming, (2) 1,200 W, 10 amp dimming channels. Controlled by farm computer, 0-10V DC input signal or manually.

Product specs:

- 120 VAC, 60 Hz
- 172mm Depth x 84.4mm Length x 202mm Width
- Operating temperature -20°C to 40°C / -4°F to 104°F
- Product weight per piece 2.68kg/5lbs
- Ratings and Certifications: UL/CSA

Order number: SKU1000001041

Description: PLS MR4 2400 STD, 120VAC



We're excited to help you find the perfect product for your needs. On this page, we'll guide you through the process of purchasing our products, from selecting the right item to checking out and receiving your order.

1

STEP 1: BROWSE OUR PRODUCT SOLUTIONS AND OFFERINGS

The first step in buying our products is to browse our selection. You can find our products in this catalog and also online at www.once.lighting. Our website is easy to navigate, with clear categories and filters to help you find what you're looking for. Our dedicated animal lighting experts are here to help you with a lighting plan for your barn or operation, please reach out at +1 (763) 297-9179.

2

STEP 2: SELECT THE RIGHT ITEM

Once you've found a product you're interested in reach out to our customer service team for a quote at +1 (763) 297-9179. We are ready to assist you during standard business hours, Monday-Friday, 8AM-4PM central time.

3

STEP 3: WHERE TO BUY

Once you've selected the right item, contact your Once by Signify account manager or your local equipment dealer. If you have any questions regarding installation, don't hesitate to reach out to our customer service team or your account manager.

Find a Once by Signify Account Manager near you;

America

- Western US | Aqua, Broiler, Breeder, Duck, Pullet, Turkey – Chad Teer, chad.teer@signify.com
- Eastern US | Aqua, Broiler, Breeder, Duck, Pullet, Turkey – Jason King, jason.king_1@signify.com
- Layer – Dyke Addis, dyke.addis@signify.com
- Aqua, Swine, Biosecurity – Pat Murphy, pat.murphy@signify.com

Europe – Sebastian Haskamp, sebastian.haskamp@signify.com

LATAM – Ramiro Robles, ramiro.robles@signify.com

Canada – Pat Murphy, pat.murphy@signify.com

LOOKING FOR LIGHTS FOR AQUACULTURE, HORTICULTURE OR CANNABIS?

Contact us at once.info@signify.com and we will connect you to the right team!

We hope this guide has helped you understand how to buy our products. If you have any further questions or concerns, don't hesitate to contact us. We're always here to help you find the perfect product for your needs.

©signify

Our global brands are

PHILIPS interact **once**



FARMER BOY[®]

50 West Stoever Ave. | Myerstown, PA 17067 | 1-800-845-3374

www.farmerboyag.com