

Model 367-1 Heat Lined Incinerator

- Dimensions 36 in. diameter x 7 ft. length
- .375 tank thickness
- Reinforced with 2x1 solid bar
- Load capacity 700 lb
- 35 cubic foot chamber
- Diesel, Propane, or Natural Gas Burner option
- Voltage requirements 120 volt 60 HZ 20 Amp
- Adjustable 12 hour timer
- Unit is lined with repairable refractory block rated for 3000 degree temperature
- Door is lined with 3 inches of ceramic fiber insulation rated for 2500 degree temperature
- Life expectancy of the liner is 5,000-7,500 hours
- Main chamber is equipped with patented heat control shut off and digital read-out controller
- Unit has removable end plate for your convenience when installing a replacement liner
- Loading door size is 48 in, 42in, 36in, length x 18 in. width
- Door is equipped with counterweight
- Unit has a burn rate of 75-100 lb per hour when loaded properly
- Includes 3ft x 6in sch 40 exhaust stack
- Burning temperature is 1325-1400F
- Shipping weight is 2650 lb

Optional Accessories

- Cleanout Door
- Door seal Gasket
- Locking Door Clamps
- EPA certified afterburner
- Air quality secondary chamber
- Winch assisted door opener
- Load assisting winch
- Grates
- Heavy Duty Refractory Liner
- Custom built accessories upon request
- Exhaust stack extensions

